




## VKP60

### 60mm Ultra-Compact Receipt/Ticket Kiosk Printer

VKP60 is the kiosk printer for **receipt and ticket** printing. Thanks to its **multiple configurations**, it is suitable for a wide variety of self-service applications. Compact, versatile, and provided with useful features such as **anti-jamming, full and partial cutting**, this device can be employed in any type of kiosk thanks to its adjustable two-position roll holder. VKP60 is available in three different configurations: **compact, paper mouth** and **presenter**.



12 mm spindle wireless roll holder



Wireless roll holder + bracket for VKP60 Presenter



Bracket for wireless roll holder for VKP60 Compact/Paper mouth



Roll holder bracket with NPE for VKP60 PRESENTER



Wireless roll holder



VKP60 ADAPTER TO 12 VDC

DONGLE RS232 VKP60

DONGLE ETH VKP60

TG2460 bracket adapter Kit for VKP60 Paper mouth


## ACCESSORIES

- Roll holder bracket VKP60 with NPE
- Roll holder bracket wireless VKP60 Compact
- Roll holder bracket wireless VKP60 Presenter
- Roll holder bracket VKP60 Presenter with NPE
- Wireless roll holder VKP60
- VKP60 adapter to 12Vdc
- VKP60 compatible TG2460 fixing kit
- Dongle ETH VKP60
- Dongle RS232 VKP60
- Power supply 24V 60W connector DIN

## TECHNICAL SHEET

	VKP60 - Compact	VKP60 - Paper Mouth	VKP60 - Presenter
<b>Resolution</b>	203 dpi		
<b>Power supply</b>	24V, 12V adapter (optional)		
<b>Printing speed</b>	up to 200 mm/s @24V		
<b>Paper thickness</b>	50 - 130 $\mu$ m		50 - 100 $\mu$ m
<b>Roll diameter</b>	max. 100 mm (with CUSTOM roll holder)		
<b>Paper width</b>	44, 50, 54, 58, 60 mm		
<b>Cutter</b>	Total and partial cut		Total cut
<b>Interfaces</b>	USB 2.0, Virtual Com, RS232 or ETH (optional)		
<b>Sensors</b>	Paper present, cover open, printhead temperature, cutter home, black mark, anti-jam, optional: near paper end	Paper present, cover open, printhead temperature, cutter home, black mark, paper in output, optional: near paper end	
<b>Character set</b>	PC437, PC850, PC858, PC860, PC862, PC863, PC864, PC865, PC866, Katakana, WPC1250, WPC1251, WPC1252, WPC1253, WPC1254, WPC1255, WPC1256, WPC1257, WPC1258, Chinese GB18030, Korean PC949		
<b>Supported barcodes</b>	UPC-A - UPC-E - EAN13 - EAN8 - CODE39 - ITF - CODABAR - CODE93 - CODE128 - CODE32 Codice QR - Aztec - PDF417 - Datamatrix - GS1 Databar		
<b>Print head life</b>	200 km / 100M pulses		
<b>Cutter life</b>	1M		
<b>LED paper mouth</b>	No	Default	
<b>Drivers</b>	Windows® (32/64 bit), CUPS Linux (32/64 bit), OPOS, Java POS, Status Monitor SDK		
<b>SW tools</b>	PrinterSet, CPT, Windows® API, Driver Manager, Android™ API, iOS API		
<b>Operative temperature</b>	-20 to +70°C ; 10 to 90% RH (no condensation)		
<b>Dimensions</b>	86 mm (W) x 58 mm (D) x 81 mm (H)	86 mm (W) x 78.5 mm (D) x 89.5 mm (H)	109.8 mm (W) x 99 mm (D) x 87.3 mm (H)
<b>Weight</b>	330 g	340 g	453 g

## MODELS



**915NA010100300**

PRINTER VKP60 USB RS232  
COMPACT



**915NA020100300**

PRINTER VKP60 USB RS232  
PAPER MOUTH



**915NA030100300**

PRINTER VKP60 USB RS232  
PRESENTER

---

Via Berettine, 2 - 43010 Fontevivo PR - VAT: IT02498250345 - TEL: +39 0521 680111 - FAX: +39 0521 610701 - UNIQUE CODE: 8RQN7AZ

The technical data on this website are not binding and may be changed without advanced notice.

Last update: 18 July 2025